Easy PRO



The compact and versatile best selling machine

The most imitated change machine of the range has been entirely renovated and is now even more secure and reliable, thanks to the connection of installed peripherals via ccTalk. The 32-bit CPU provides functions normally present only on change machines of higher range and price, such as importing/exporting configuration parameters, exporting accounting data and the useful function of machine cloning. The reinforced closing mechanisms make Easy PRO one of the most secure change machines on the market with respect to attempts of tampering and fraud. The COMESTERO Easy PRO fits perfectly into all environments: shopping centres, gyms, airports, service stations, arcades, offices, bars and internet cafés.

Highlights

- Distribution of coins or tokens. Coins/tokens dispensed automatically or manually
- · Bonus function for tokens
- · Connection of peripherals via ccTalk
- · New 32-bit CPU with SD-Card
- Exporting of accounting data and importing of configuration parameters via SD-Card
- · Machine cloning function
- · Internal on/off controls to prevent tampering
- Pivoting door to facilitate dispenser-loading and cash box removal operations
- · Special cover for the dispenser's extension: prevents coins from falling out in the event that the machine is tipped over
- Holes in the cabinet for fastening the unit to other machines or to external structures such as columns or pillars
- · Installation options:
 - wall mounted (with the Easy UP kit)
 - countertop
 - wall mounted, by means of 3 anchoring bolts to be inserted at the back of the device
 - free standing on base (optional)



Technical Specifications

Versions	Change Machine	Change Machine on Support Base	
Dimensions (LxHxW)	257 x 473 x 353 mm	257 x 1,436 x 353 mm	
Weight	25 kg	38 kg	
Power supply	230 Vac - 50 Hz	230 Vac - 50 Hz	
Power consumption	60 W max	60 W max	
Operating temperature	3 °C ÷ 50 °C	3 °C ÷ 50 °C	

Coin Capacity	0.50 €	1.00 €	2.00 €
1 Evolution hopper with extension	2,400	2,400	2,200
Cash box		1,600	